

पाधिकार से प्रकार PUBLISHED BY AUTHORITY

सं० 32]

नई दिल्ली, शनिवार, अगस्त 10, 1996 (श्रावण 19, 1918)

No. 32]

NEW DELHI, SATURDAY, AUGUST 10, 1996 (SRAVANA 19, 1918)

इस माग में भिन्न पुछ संख्या दी जाती है जिससे कि यह अलग संकलन के रूप में रखा जा सके [Separate paging is given to this Part in order that it may be filed as a separate compilation]

भाग III~-रञ्जण्ड 2 **IPART III—SECTION 21**

पेटेन्ट कार्यालय द्वारा जारी की गई पेटेन्टों और डिवाइनों से सम्बन्धित अधियुष्णाएं और नोटिस [Notifications and Notices Issued by the Patent Office relating to Patents and Designs]

THE PATENT OFFICE PATENTS AND DESIGNS

Calcutta, the 10th August 1996

ADDRESS AND JURISDICTION OF THE OFFICES OF THE PATENT OFFICE

The Patent Office has its Head Office at Calcutta and Branch Offices at Bombay, Delhi and Madras having territorial Jurisdiction on a zonal basis as shown below:-

Patent Office Branch, Todi Estates, IIIrd Floor, Lower Parel (West), Bombay-400 013,

The States of Gujarat, Maharashtra, Madhya Pradesh, Goa and the Union Territories of Daman and Diu and Dadra and Nagar Haveli.

Telegraphic address "PATOFFICE"

Patent Office Branch, Unit No. 401 to 405, IIIrd Floor, Municipal Market Building, Saraswati Marg, Karol Bagh, New Delhi-110 005.

The States of Haryana, Himachal Pradesh, Jammu and Kashmir, Punjab, Rajasthan, Uttar Pradesh, Delhi and the Union Territory of Chandigarh.

Telegraphic address: "PATENTOFIC"

Patent Office Branch 61. Wallajah Road. Madras-600 002.

The States of Andhra Pradesh. Karnataka, Kerala, Tamilnadu, Pondicherry and the Union of Territories of Laccadive, Minicoy and Anunidivi Islands.

Telegraphic address "PATENTOFIS"

Patent Office, (Head Office), "NIZAM PALACE", 2nd M.S.O. Building, 5th, 6th and 7th Floor, 234/4, Acharya Jagadish Bose Road, Calcutta-700 020.

Rest of India

Telegraphic address "PATENTS"

All applications, notices, statements or other documents or any fees required by the Patents Act, 1970 or the Patents Rules, 1972 will be received only at the appropriate Offices of the Patent Office.

Fees: -The fees may either be paid in cash or may be sent by Money Order or payable to the Controller at the appropriate Offices or by bank draft or cheque payable to the Controller drawn on a scheduled bank at the place where the appropriate office is situated.

पेटॉंट कार्यालय

एकस्य सथा अभिकल्प

कलकसा, दिनांक 10 अगस्त 1996

पेटेंट कार्यालय के कार्यालयों के पत्ते एवं क्षेत्राधिकार

पेट'ट कार्णालय का प्रधान कार्यालय कलकते में अवस्थित हैं तथा बम्बई, दिल्ली एवं महास में इसके शाखा कार्यालय हैं, जिनके प्रावृद्धिक क्षेत्राधिकार जीन के आधार पर निम्न रूप में प्रदृशित हैं:

पेटेंट कार्यालय शासा, टोडी इस्टेट सीसरा तल, लोअर परेल (पश्चिम), बम्बर्ड-400013।

गुजरात, महाराष्ट्र तथा मध्य प्रदेश तथा गाँआ राज्य क्षेत्र एवं संघ शासित क्षेत्र, दमन तथा दीव एवं दावर और नागर हुनेती ।

तार पता-"पेटोफिसे"

पैटंट कार्यालय शाखा, एकक सं. 401 सं 405, तीसरा तल, मगरपालिका बाजार भवन, सरस्वती मार्ग, करोल बाग, मर्झ दिल्ली-110005।

हरियाणा, हिमाचल प्रदोश, जम्मू तथा कश्मीर, पंजाब, राजस्थान, उत्तर प्रदोश तथा दिल्ली राज्य क्षेत्री एवं संच बासित क्षेत्र चण्डीगळ ।

तार पता-"पट टीफिक"

CORRIGENDUM

The name of the Controller General of Patents, Designs & Trade Marks has been wrongly printed in the Gazette of India. Part-III, Section 2 at Page No. 155 Column 2 dated 10-2-96, Page-168 Column 2 of 17-2-96, Page 176 Column 2 of 24-2-96, Page 188 Column 2 of 2-3-96 and Page 321 Column 2 of 20-4-1996 as R. A. ACHARYA Instead of T. R. SUBRAMANIAN.

APPLICATION FOR PATENT FILED AT THE HEAD OFFICE 234/4, ACHARYA JAGADISH BOSE ROAD.

CALCUTTA-20

THE dates shown in the crecent bracket are the dates claimed under Section 135, of the Potent Act, 1970.

30-04-1996

771/Cal/96. Daewoo Electronics Co. Itd. "Apparatus for controlling reserved recording and a method thereof". (Convention No. 95-10489; on 29-4-95; in Korea).

पेट कियालिय शाखा, 61, यालाजाह रोड, मद्रास-600002 ।

> आन्ध्र प्रदेश, कर्नाटक, करेल, तिमलनाड्य तथा पांडिचेरी राज्य क्षेत्र एवं संघ शासित क्षेत्र लक्षव्वीप मिनिकाय तथा एमिनीदिवि द्वीप ।

तार पत्ता-"पैटोफिस"

पेटरेंट कार्यालय (प्रधान कार्यालय), निजास पैलेस, द्वितीय बहुत्तलीय कार्यालय, भवन, 5, 6 तथा 7वां तल, 234/4, आचार्य जगदीश बीस मार्ग, कलकत्ता-700020 ।

भारत का अवशेव क्षेत्र ।

सार पता-''पैटर्न्स''

पेटेंट अधिनियम, 1970 या पेटेंट नियम, 1972 में अपे-क्षित सभी आवेदन पत्र, सूचनाएं, विवरण या अन्य मलेख पेटेंट कार्यालय के क्षेत्रल उपयुक्त कार्यालय में शी प्राप्त किये जायेंगे।

शुल्क :—शुल्कों को अदायगी या तो नकत की आयेगी अधवा उपयुक्त कार्यालय में नियन्त्रक को भूगतान योग्य धनादेश अधवा हाक आदेश या जहां उपयुक्त कार्यालय अवस्थित है, उस स्थान के अनुस्चित बेंक से नियन्त्रक को भुगतान योग्य बेंक झाफ्ट अथवा चैक द्वारा की जा सकती है ।

- 772/Cal/96. Tejinder Singh. "A cargo handling system from ship to ship".
- 773/Cal/96. Carnegie Mellon University. "Low oxygen affinity mutant hemoglobin". (Convention No. 08/432,071; on 1-5-1995; in U.S.A.).
- 774/Cal/96. Matsushita Electric Industrial Co. Ltd. "Interface apparatus". (Convention Nos. 7-105551; on 28-4-95, 7-270828; on 19-10-95 & 7-284768; on 1-11-95; in Japan).
- 775/Cal/96. Owens Corning. "Irregularly shaped glass fibers and insulation therefrom". (Convention No. 08/434,620; on 4-5-95; in U.S.A.).
- 776/Cal/96. Owens Corning. "Irregularly shaped glass fibers and insulation therefrom". (Convention No. 08/434,699; on 4-5-95; in U.S.A.).
- 777/Cal/96. Hoechst Aktiengesellschaft. "Isoindoline nigments based on aminoquinoxalinediones". (Convention No. 19516804.6; on 8-5-95; in Germany).
- 778/Cal/96. Dystar Japan Ltd. "Textile dye preparation". (Convention No. 19519356.3; on 26-5-95; in Germany).
- 779/Cal/96. Metallgesellschaft Aktiengesellschaft. "Process of removing no from nitrosvi hydrogensulfate". (Convention No. 19516303.6; on 4-5-95; in Germany).

780/Cal/96. Siemens Automotive Corporation. "Armature guide for an electromechanical fuel injector and method of assembly". (Convention No. 08/444,497; on 19-5-95; in U.S.A.

- 781/Cal/96. Scitex America Corp. "A system and method for computer to press printing". (Convention No. 08/434,448; on 3-5-95; in U.S.A.).
- 782/Cal/96. Japan Tobacco Inc. "Monoclonal antibody reactive to human cholestrol ester transfer protein and assay method for human cetp". (Convention No. 134836/1995; on 2-5-95; in Japan).
- 783/Cal/96. Soon Yoon Han, "Carbon brush holder". (Convention No. U95-9266; on 2-5-95; in Rep. of Korea).
- 784/Cal/96. Aimbridge Pty, Ltd. "Hinge". (Convention Nos. PN 3027; on 17-5-95 & PN 4676; on 9-8-1995; in Australia).
- 785/Cal/96. Bando Chemical Industries, Ltd. & Honda Giken Kogyo Kabushiki Kaisha. "Cogged vbelt". (Convention No. 7-107251; on 1-5-95; in Japan).

1-5-1996

- 786/Cal/96. Innapharma, Inc. "Trl-, tetra-, penta-, and poly-peptides, method of manufacturing the same and their therapeutic use as an antidepressant agent". (Convention No. 08/432,651; 2-5-95; in U.S.A.).
- 787/Cal/96. Dr. Anil Krishna Kar. "A method for producing fibre reinforced cement concrete".
- 788/Cal/96. Koyo Sangyo Co, Limited, "A laminated material".
- 789/Cal/96. General Electric Company, "Method for brazing rotor bars to end rings of a rotor for an asynchronous AC motor".
- 790/Cal/96. The University of Queensland. "Aluminium alloy powder blends and sintered aluminium alloys". (Convention No. PN2736; on 2-5-95; in Australia).
- 791/Cal/96. Hoechst Aktiengesellschaft. "Process for the prepartion of hydroxybiarylphosphines, and novel compounds of this group of substances". (Convention No. 19521340.8; on 12-6-95; in Germany).
- 792/Cal/96. Hoechst Aktiengesellschaft. "Plastic with reduced sulfur uptake rate". (Convention No. 19516701.5; on 10-5-95; in Germany).
- 793/Cal/96. Johnson & Johnson Vision Products, Inc.
 "Multifocal lens designs with intermediate optical powers". (Convention No. 08/433 737; on 4-5-95; in U.S.A.).
- 794/Cal/96. Johnson & Johnson Vision Products, Inc. "Concentric lens designs for astigmatic presbyopes". (Convention No. 08/433 844; on 4-5-95; in U.S.A.).
- 795/Cal/96. Johnson & Johnson Vision Products, Inc. "Concentric ring single vision lens designs". (Convention No. 08/433 842; on 4-5-95; in U.S.A.).
- 796/Cal/96. Johnson & Johnson Vision Products, Inc. "Concentric annular ring lens designs for astigmatism". (Convention No. 08/433 741; on 4-5-95; in U.S.A.).
- 797/Cal/96. Johnson & Johnson Vision Products, Inc.
 "Aspheric toric lens designs". (Convention No. 08/433/742; on 4-5-95; in U.S.A.).
- 798/Cal/96. Hitachi Ltd. "Method of correcting deflection defocusing in a crt, a crt employing same, and an image display system including same cr.".

 (Convention No. 7-114755; on 12-5-95; in Japan).

799/Cal/96. Windmoller & Holscer. "Doctor blade arrangement for a rinse inking unit of a rotary printing machine". (Convention No. 19516223.4; on 3-5-95; in Germany).

2-5-1996

- 800/Cal/96. Corporated Ceramists ... Private Limited. "A process for making ferro-manganese agglomerates from industrial wastes".
- 801/Cal/96. Lechner GmbH. "Method for the manufacture and/or filling of a two-chamber pressure pack". (Convention No. 195 16 100.9; on 5-5-95; in Germany).
- 802/Cal/96. Eli Lilly and Company. "Single chain insulin with high bioactivity", (Convention Nos. 08/435, 762; on 5-5-95 & 08/435,503; on 5-5-95; in U.S.A.).
- 803/Cal/96. Johnson & Johnson Medical, Inc. "Device for vapor sterilization of articles having lumens". (Convention No. 08/436999; on 8-5-95; in U.S.A.).
- 804/Cal/96. Siemens Aktiengesellschaft, "Memory management meihod". (Convention No. 19516667.1; on 5-5-95; in Germany).
- 805/Cal/96. Sven Siegle. "Procedure of manufacturing a pulp from cellulose containing material, the pulp itself and its uses". (Convention No. 19516151.3; on 3-5-95; in Germany).
- 806/Cal/96. Hoechst Celanese Corporation. "Catalyst for vinyl acetate manufacture". (Convention No. 08/449,604; on 23-5-95; in U.S.A.).
- 807/Cal/96. Brooke Bond Lipton India Limited, "Ice containing confection".
- 808/Cal/96. David Bland Pierce. "Tube finning machine and method and product". (Convention Nos. 9508921.5; on 2-5-1995; and 9518663.1; on 13-9-1995; in United Kingdom).
- 809/Cal/96. Tana Shin Denbi Co. Ltd. "Disc playing apparatus". (Convention No. 8-54146; on 17-2-96; in Japan).
- 810/Cal/96. Ishikawajima-Harima Heavy Industries Company Limited, and BHP Steel (JLA) Pty. Ltd. "Casting steel strip". (Convention Nos. PN 2811; on 5-5-1995 & PN 4748; on 11-8-95; in Australia).
- 811/Cal/96. Philip Environmental Services Corporation, and Westinghouse Electric Corporation. "Process for recovering metals from iron oxide bearing masses". (Convention No. 08/434,372; on 3-5-95; in U.S.A.).
- 812/Cal/96. Silicon Graphics, Inc. "Source synchronous clocked data link". (Convention No. 08/435,453; on 5-5-95; in U.S.A.).

6-5-1996

- 813/Cal/96. Mr. Jayanta Kar. "Heat sensitive and selfcuring stickers (Logo), symbol & letters etc.) to be manufactured under both hot and cold vulcanasation system".
- 814/Cal/96. Dawoo Electronics Co. Ltd. "Method for forming array of thin film actuated mirrors", (Convention Nos. 95-13352 & 95-13353; on 26-5-1995; in South Korea).
- 815/Cal/96. Dawoo Electronics Co. Ltd. "Thin film actuated mirror array and method of manufacturing the same". (Convention Nos. 95-13358 & 95-13360; on 26-5-95; in South Korea).
- 816 Car/96. Daewoo Electronics Co. Ltd. "Pulsator assembly for a washing machine". (Convention No. 95-22381; on 27-7-1995; in Korea).

- 817/Cal/96. Sandip Agarwal. "An improved method and an automatic machine to make button lac and button lac made therefrom".
- 818/Cal/96. Innovative Enterprises Limited. "Pressure indicating device".
- 919/Cal/96. Kasei Optionix Ltd. "High resolution cathode ray tube". (Divisional to out of No. 630/Cal/92; dated 02-09-92).
- 820/Cal/96. The Babcock & Wilcox Company. "Field serviceable fill tube for use on heat pipes". (Convention No. 08/539, 397; on 05-10-95; in U.S.A.).
- 821/Cal/96. The University of Sheffield. "Improvements in or relating to reinforced concrete structural elements, and method of preparing the same". (Convention No. 9509115.3; on 04-05-95; in United Kingdom).
- 822/Cal/96. Recordati S.A. "A process for the preparation of lorcanidipine hydrochloride". (Convention No. MI95A 000957; on 12-05-1995; in Italy).
- 823/Cal/96. Hitachi Ltd. "Method for estimating discharge capability of zinc oxide power element, method for screening the element and systems for carryinging out these methods". (Convention No. 07-113345; on 11-05-95; in Japan).
- 824/Cal/96. Hitachi, Ltd. "Semiconductor device and process for producing the same". (Convention No. 07-109585; on 08-05-95; in Japan).
- 825/Cal/96. Matsushita Electric Industrial Co., Ltd. "Apparatus and method for charging three-component mixed refrigerant". (Convention No. 07-115504; on 15-05-95; in Japan).
- 826/Cal/96, Kuraray Co., Ltd. "Polyvinyl alcohol-based fiber and manufacturing thereof". (Convention No. 122132/95; on 22-05-95; in Japan).
- 827/Cal/96. Merck Patent Gesellschaft Mit Beschrankter Haftung. "Colour Pigments". (Convention No. P19516960.3; on 12-05-95; in Germany).
- 828/Cal/96. Emitec Gesellschaft Fur Emissionstechnologie mbH. "Apparatus and process for producing a honcycomb body". (Convention No. 19521685.7; on 14-06-95; in Germany).
- 329/Cal/96. W. Schlafhorst Ag & Co. "Method for can spinning". (Convention No. P19523835.4; on 30-06-95; in Germany).
- 830/Cal/96. Emitec Gesellschaft Fur Emissionstechnologie mbH. "Electrically insulating gas-tight penetration". (Convention No. 19520758.0; on 7-6-95; in Germany).
- 831/Cal/96. General Electric Company. "Junction component for connecting the electrical leads of a printed circuit board and a separate celetrical unit". (Convention No. P9501469; on 19-05-95; in Hungary).
- 832/Cal/96. (1) Helmut Bacher, (2) Helmuth Schulz, and (3) Georg Wendelin. "Apparatus for filtering plasticized thermoplastics and filter element for an apparatus for this kind".

ALTERATION OF DATE UNDER SECTION-16

176629 (779/Cal/91) antedated to 27th October 1988.

176630 (780/Cal/91) antedated to 27th October 1996.

COMPLETE SPECIFICATION ACCEPTED

Notice is hereby given that any person interested in opposing the grant of patents on any of the Applications concerued, may, at any time within four months of the date of this issue or within such further period not exceeding one month applied for on Form-14 prescribed under the Patents Rules 1972 before the expiry of the said period of four months, given notice to the Controller of Patents at the appropriate office on the prescribed Form-15, of such opposition. The written statement of opposition should be filed alongwith the said notice or within one month of its date as prescribed in Rule-36 of the Patents Rules, 1972.

The classifications given below in respect of each specification are according to Indian Classification and International Classification.

Typed or photo copies of the specifications together with photo copies of the drawings, if any, can be supplied by the Patent Office, Calcutta or the appropriate Branch Office on payment of the prescribed copying charges which may be ascertained on application to that office. Photo copying charges may be calculated by adding the number of pages in the specification and drawing sheets mentioned below against each accepted specification and multiplying the same by two to get the charges as the copying charges per page are Rs. 2/-.

स्वीकृत सम्पूर्ण विनिन्दंश

एतद्वारा यह सूचना दी जाती है कि सम्बद्ध आवेदनों में से किसी पर पेटेंट अनुदान के विरोध करने के हुच्छुक कोई व्यक्ति, इसके निर्गम की तिथि से चार (4) महीने या अग्रिम एसी अवधि जो उक्त 4 महीने की अवधि की समाध्ति के पूर्व पेटेंट निषम, 1972 के तहत विहित प्रयत्र 14 पर आवेदित एक महीने की अवधि से अधिक न हो, के भीतर कभी भी नियन्त्रक, एकस्य को उपयुक्त कार्यालय में एसे विरोध की सूचना विहित प्रयत्र 15 पर दे सकते हैं। विरोध सम्बन्धी लिखित वन्तव्य, उक्त सूचना के साथ अथवा पेटेंट नियम, 1972 के नियम 36 में यथा विहित इसकी तिथि के एक महीने के भीतर ही फाइल किए जाने वाष्ट्राएं।

"प्रत्येक विनिर्दश के संदर्भ में नीचे दिए बर्गीकरण, भारतीय वर्गीकरण तथा अन्तर-राष्ट्रीय बर्गीकरण के अनुरूप हैं"।

स्पांकन (चित्र आरेखां) की फोटो प्रतियां चिट्ट कार्याक्त की टिक्कित अथवा कोटो प्रतियों की आपूर्ति पेटेंट कार्यालय, कलकता अथवा उपयुक्त शासा कार्यालय द्वारा विद्यत्त स्थान कार्यालय द्वारा विद्यत्त सामा कार्यालय द्वारा विद्यत्त स्थान करने के उपरान्त उसकी अवायगी पर की जा सकती है। विनिद्धां की पृष्ट संस्था के साथ प्रत्येक स्वीकृत विनिद्धां के सामन नीचे बणित चित्र आरेस कागजों को जोड़कर उसे 2 से गुणा कर कै, (अपिक प्रत्येक पृष्ट का निष्यान्तरण प्रभार 2/- रह. है) फोटो तिक्याकरण प्रभार का परिकारन किया जा सकता है।

Cl.: 172 D-4

176511

Int. Cl.: D 01 4 1/18.

"A SPINNING MACHINE".

Applicant & Inventors: FRITZ STAHLECKER OF JOSEF-NEIDHART-STRASSE 18 7347 BAD UBERKIN-GEN, FRG.

AND

HANS STAHLECKER OF HALDENSTRASSE 20 7334 SUSSEN FRG.

Application No.: 574/Cal/1991 filed on 1st August 1991

Appropriate Office for Opposition Proceedings Patent Rule 1972), Patent Office, Calcutta. (Rule 4,

10 Claims

A spinning machine comprising :

a spinning machine having a plurality of machine sections disposed adjacent one another longitudinal extent of the spinning machine, each spinning machine section including a plurality of spinning stations arranged on each of both sides of a spinning machine centre plane,

a sliver can support plat form disposed above the spinning stations,

sliver supply cans arranged in a plurality of rows on the platform, and

sliver guiding apparatus for guiding sliver between the respective supply cans and spinning stations,

wherein said sliver guiding apparatus including :

respective conveyor belts for guiding at least one sliver from a supply can and a spinning station,

support guide rollers for the respective conveyor bells, and

at least one support for supporting the support guide rollers and

wherein the at least one support includes a support supported at and extending upwardly from the spinning machine frame through the platform to support the support guiderollers, at a location disposed above the supply cans said support being disposed between two of said machine sections and serving to support guide rollers, wherein said sliver guiding apparatus further includes respective slides facing respective vertical sections of each conveyor belt with said slides and conveyor belts engaging respective opposite slides of two sliver.

(Compl. Specu. 14 pages;

Drgs. 3 sheets.)

176612

Cl4 : 201 B

Int. Cli.: C 02 F 11/08.

"A PROCESS FOR OBTAINING LIQUID INDUSTRIAL WASTE FREE OF COMBUSTIBLE MATERIALS BY WET OXIDATION TREATMENT OF AQUEOUS

Applicant: ZIMPRO PASSAVANT ENVIRONMENTAL SYSTEMS, INC., OF 301 WEST MILITARY ROAD ROTHSCHILD, WISCONSIN 54474, UNITED STATES OF AMERICA.

Inventors: GENE WALTER MUELLER; BRUCELEE BRANDENBURG.


Application No.: 585/Cal/1991 filed on 2nd August. 1991.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta.

2 Claims

A process for obtaining liquid industrial waste free of combustible materials by wet oxidation treatment of aqueous waste containing combustible materials, said process comprising the steps of:

- (a) mixing an oxygen-containing gas with to form an influent for wet oxidation;
- (b) sequentially passing said influent through a first heat exchanger, a second heat exchanger and then into a reaction vessel for wet oxidation;
- (c) passing super heated steam through said second heat exchanger to heat said influent to a tempera-ture in the range of about 200 degrees Fahrenheit to about 480 degrees Fahrenheit sufficient to initiate the desired exothermic wet oxidation reaction in said reaction vessel and for a start-up time period sufficient to cause the wet oxidation reaction in said reaction vessel to substantially stabilize;
- (d) withdrawing an oxidized effluent from said reaction vessel and passing said effluent through said first heat exchanger to preheat said influent to a temperature sufficient to initiate the wet exidation reaction; and
- (e) after said start-up period, adjusting the temperature and flow of the superheated steam passing through said second heat exchanger to adjust the temperature of said preheated influent to level suitable for continued steady state of operation in the range of about 300 degrees Fahrenheit to about 700 degrees Fahrenheit in said reaction vessel.



(Compl. Specn.; 12 pages;

Drgns. : 1 sheet.)

IC1. : 40 H

176613

Int.: Cl⁴: B 01 D 53/34.

"PROCESS AND APPARATUS FOR REMOVING NO, FROM GAS STREAMS".

Applicant: CUMMINS POWER GENERATION, INC., 500 JACKSON STREET COLUMBUS, INDIANA 47202, UNITED STATES OF AMERICA.

Inventors: RALPH J. SLONE.

Application No.: 680/Cal/1991 filed on 9th September,


Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta.

19 Claims

A process for producing a gas stream containing reduced NOx comprising the steps of :

producing NCO radicals outside an NOx - containing gas stream;

and adding said NCO radicals directly to the gas stream to reduce the NO_x content of the gas stream by reaction with said NOx.



(Copl. Speen. ; 19 pages;

Drgns: 1 sheet.)

Cl.: 199

176614.

Int, CJ.4: F 16 K 33/00, G 05 D 9/02.

SAFETY DEVICE FOR THE WATER CARRYING DOMESTIC APPLIANCES.

Applicant: BOSCH-SIEMENS HAUSGERATE GMBH, OF HOCHTSTRASSE 17, D-8000 MUNCHEN 80, GER-MANY.

Inventors: (1) ERNST STICKEL (2) RUDIGER ELER-MANN (3) HELMUT JERG.


Application No.: 692/Cal/1991 filed on 12th September 1991.

Appropriate office for opposition proceedings (Rule 4, patent rule 1972) Patent Office Calcutta.

11 Claims

A safety device for the water carrying domestic appliances, with a fluid container, a filling control, an inlet valve which can be opened by a control mechanism aid/or can be shut by the program control machnism, a scouring pump and a safety level switching off device, where a floater is situated in a chamber joined in a fluid carrying way with the fluid container, the chamber having an opening for the entry of water and operates a switch in the switch position, the switch switches on the scouring pump in switch position and if required, shuts the inlet valve wherein the floater (16) is kept at a short distance (a) above the static (3) of the filling of the fluid container and the switch (17) loaded on the floater (16) switches off the scouring pump (33) on reaching the steady state after the preceding acceptance of the switch position and the inlet valve (32) is kept shut after that.





(Compl. Specn.: 15 pages

Drgns.: 1 sheet)

Cl: 144

176615.

In. Cl.4: C 09 D 5/46.

EPOXY POWDER COATING COMPOSITION FOR USE IN ELECTROSTATIC COATING.

Applicant: SOMAR CORPORATION, OF 11-2, GINZA 4-CHOME, CHUO-KU TOKYO, JAPAN.

Inventor: (1) KUNIMITSU MATSUZAKI (2) SEITARO IWAMOTO (3) TAKESHI WATANABE (4) KAZUYA ONO (5) KATSUJI KITAGAWA.

Application No.: 946/Cal/1991 filed on 24h December, 1991.

Appropriate office for opposition proceedings (Rule 4, patent rule 1972) Patent Office Calcutta.

2 Claims

A powder coating composition comprising a particulate material consisting of particles having a particle size in the range of 3-180 um and a volume resistivity of at least 107 ohm cm and each containing an epoxy resin and a curing agent for the epoxy resin such as herein described and a charge controlling agent selected from the group consisting of an acrylic resin having an average particle size in the range of 0.05-1 um and silica whose primary particles having an average particle size in the range of 2-500 um, the amount of said charge controlling agent being 0.01-10% based on the total weight of said particulate material and said charge controlling agent, and said charge controlling agent being present on surfaces of said particles of said particulate material the curing agent is used in an amount of 0.5-70 parts by weight per 100 parts by weight of the epoxy resin.

(Compl. Specn.: 14 pages

Drgns: Nil)

Cl.: 32 Fan

176616

Int. Cl. : C 07 B 41/08 + C 11 C 1/00

PROCESS FOR HYDROLYSING FATS AND OILS (TRIGLYCERIDES).


Applicant: BALMER LAWRIE & COMPANY LIMITED, OF 21, NETAII SUBHAS ROAD, CALCUTTA-700 001, WEST BENGAL, INDIA. Inventors: CHENGAZHAPALLIL VELUPILLAI CHANDRASEKHARAN. DEBASISH SEN GUPIA.

Application No. 612/Cal/1992 filed on 8th January, 1992.

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcutta,

4 Claims

Process for dyarolysing fats oil (Triglycerides) which comprises treating the fats and oils with 0.1 to 10% by wt. of an ester as non-ionic hydrolytic agent at a temperature of 15 to 120°C in the presence of 0-50% water on weight of the fat/oil whereby the fat/oil plits into fatty acids and glycerine and removing the fatty acid and glycerine from the reaction mass employing conventional technique, wherein the said ester has the following structural formula—



Wherein X_1 , X_2 are functional groups like H, CH₂, indolyl, hydroxy X_3 is a functional group having one or more hetero atoms like NH₂, SH;

R is an alkylene groups having 2 to 200 carbon atoms.

(Compl. Speen, 9 pages,

Drgns. Nil.)

Cl. 32 F 2c

· 176617

Int. Cl.4: C 07 C 147/12

IMPROVED PROCESS FOR THE PREPARATION OF 3-AMINOPROPYL 2-SULFATOETHYL SULFONE.

Applicant: HOECHST AKTIENGESELLSCHAFT, OF D-6230 FRANKFURT AM MAIN 80, FEDERAL REPUBLIC OF GERMANY.

Inventors: (1) MICHAEL MEIER, (2) HEINRICH ANGENENDT, (3) GEORGE GROTSCH.

Application No. 045/Cal/1992 filed on 27th January, 1992.

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcutta.

9 Claims

An improved process for the preparation of 3'-aminopropyl 2-sulfatoethyl sulfone in high yield, which comprises reacting allylamine with mercaptoethanol in aqueous solfuric acid in a one-pot process at temperatures from 25°C to the boiling point of the reaction mixture in the presence of free-radical initiators 2, 2'-azobis [2-(2-imidazolin-2-yl) propanel] or its dihydrochloride which are soluble in the reaction medium, oxidizing the reaction mixture thus obtained with hydrogen peroxide in the presence of catalytic amounts of a compound of a transition metal of the periodic table of elements as oxidation catalyst as herein described to give 3'-aminopropyl 2-hydroxyethyl sulfone hemisulfate, adding further saifuric acid until the total amount of sulfuric acid in the mixture is at least 1 mol, relative to the allylamine used, and esterfying

the 3 aminopropyl 2 hydroxyethyl sulfone hemisulfate obtained after oxidation by evaporation to dryness or with sulfuric acid or oleum or chlorosulfonic acid in solution.

(Compl. Specn. 13 pages,

Drgns. Nil.)

Cl. 32 F 3b 55 E 4

175618

Int. Cl.4: C 07 D 339/04

A PROCESS FOR THE PREPARATION OF CRYSTAL-LINE THIOCTIC ACID.

Applicant: ASTA MEDICA AKTIENGESELLSCHAFT, OF WEISMULLERSTRASSE 45, 6000 FRANKFURT (MAIN) 1, GERMANY.

Inventors: (1) THOMAS BEISSWENGER, (2) HORST BETHGE, (3) FRANK HUBNER, (4) JOACHIM GOEDE, (5) KLAUS HUTHMACHER, (6) HERBERT KLENK (7) ROLAND MOLLER.

Application No. 504/Cal/1993 filed on 1st September 1993.

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcutta.

2 Claims

A process for the preparation of crystalline thioctic acid comprising.

- (a) oxidizing dimercaptooctanic acid sodium salt to sodium salt of alpha-lipoic acid,
- (b) treating said sodium salt of alpha-lipoic acid with mineral acid such as herein described to give alpha-lipoic acid (thioctic acid) and crystallising the thioctic acid characterized in that one part of said thioctic acid is dissolved at 10°C to 60°C n 5-20 parts organic solvent or organic solvent mixture such as herein described and is cooled within 2-10 hours to 0°C to -20°C, the organic solvent or solvent mixture having a dielectric constant epsilon between 2.5 and 5.5.

(Compl. Specn. 12 pages,

Drgns. 4 pages.)

C1. 55 P

176619

Int. Cl.4: A 61 K 35/02

METHOD FOR THE PRODUCTION OF A MEDICINAL COMPOSITION FOR THE TREATMENT OF CANCER.

Applicant & Inventor: NIRANJAN KUMAR SEN, OF ANANDANAGAR, P.O. BHATTANAGER, LILUAH, HOW-RAH-711 203, West Bengal, India,

Application No. 73/Cal/1995 filed on 28th June, 1995.

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcutta.

2 Claims

A method for the production of a medicinal composition for the treatment of cancer which comprises crushing and grinding together 75% by wt. of leaves and stems of the plant named hemigraphis hirts T. And (MUSAKINI) and 5% by wt. of the leaves and stems of the plant named Vitex negundo Linn. (NISINDA) with waster to obtain a pasty mass, adding to the said pasty mass powdered sodium chloride in an amount of 20% by wt. of the said leaves and stems, shaping the said mass into tablets or pills and finally drying the said tablest or pills in air.

(Compl. Specn. 5 pages,

Drgns, Nil.)

176620

CL 58 C

Int. Cl.4: F 06 B 9/26

WINDOW COVERING.

Applicant: HUNTER DOUGLAS INTERNATIONAL N.V., OF KAYA FLAMBOYAN 22 WILLEMSTAD, CUROCAO, NETHERLANDS, ANTILLES.


Inventors: (1) WENDELL BALL COLSON, (2) PAUL GERARD SWISZCZ.

Application No. 408/Cal/1991 filed on 29th May, 1991.

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcutta.

19 Claims

A window covering comprising a first sheet of relatively translucent material, a second sheet of relatively translucent material disposed parallel to said first sheet, and a plurality of strips of relatively opaque material, each strip having edge portions bonded to said first sheet and said second sheet, respectively, whereby central portions of said strips form vanes which in a first closed position of the window covering are substantially planar and extend substantially parallel to the first and second sheets effective at least partially to block transmission of light and, in a second position of the window covering, extend generally transverse to soid first and second sheets, effective to transmit light between said vanes, said first and second sheets being of different structure.



(Compl. Specn 47 pages,

Drgne. 3 sheets.)

Cl.: 145 D

176621

Int. Cl, D 21 F 5/04

APPARATUS AND METHOD FOR DRYING A WEB OF PAPER.

Applicant: BELOIT CORPORATION, OF 1 ST. LAW-RENCE AVE. BELOIT, WISCONSIN-53511, UNITED STATES OF AMERICA.

Inventors: (1) BORGEIR SKAUGEN, (2) GREGORY LYNN WEDEL.

Application No.: 1025/Cal/1990 filed on 12th December, 1990

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcut'a.

5 Claims


An apparatus (10 for drying a web (12) of paper emerging from a press section (14) of a paper machine, said apparatus (10) comprising:

a first sigle tier drying section (16) having a first plurality of drying cylinders (32, 34, 36, 38, 40, 42, 58 to 63) rotating in a first direction for drying a first side (18) of the web (12), the first drying section (16) comprising a

first plurality of vacuum transfer rolls (44, 46, 48, 50, 52, 54, 64 to 70) rotating in a direction opposite to said first direction, said vacuum transfer rolls being disposed between adjacent drying cylinders of said first plurality of drying cylinders, dryer felt means (56, 72) for conveying the web (12) in a serpontine path along said drying cylinders and said vacuum transfer rolls;

a second single tier drying section (22) following said first drying section (16) and having a second plurality of drying cylinders (94 to 99) rotating in a second direction opposite to said first direction for drying a second side (24) of the web (12) and comprising a second plurality of vacuum transfer rolls (101 to 106) rotating in a direction opposite to said second direction and disposed between adjacent drying cylinders of said second plurality of drying cylinders of said second plurality of drying cylinders (94 to 99) further dryer felt means (110) for conveying the web (12) in a serpentine path along said second plurality of drying cylinders (94 to 99) and said second plurality of vacuum transfer rolls (101 to 106) dryer transfer means (25) for transferring the web (12) without open draw from said first drying section (16) to said second drying section (22) said dryer transfer means (2) having a joint run of said felt means (72) and said further felt means (110) such that the web (12) is disposed between said felt means (72) and said further felt means (110) during passage through said joint run; and a vacuum roll (100) disposed downstream of said joint run for positively maintaining the web (12) in close conformity with said further felt means (110) when said felt means (72) and said further felt means (110) diverge relative to each other downstream of said joint run, each said vacuum transfer roll (44, 46, 48, 50, 64 to 70; 101 to 106) applying a vacuum in the range of (1 to 10 inches WC) to the web 12;

said felt means and said further felt means defining a converging nip terminating on said vacuum roll.






Fig. 4

(Compl. Specn. 44 pages,

Drgns, 9 sheets.)

Cl.: 71F, G 102 D 176622

Cl.; 71 G 102 D 176623

Int. Cl.: E 02 F 9/22.

HYDRAULIC DRIVE SYSTEM FOR HYDRAULIC MACHINE.

Applicant: HITACHI CONSTRUCTION MACHINERY CO. LTD., OF 6-2, OHTEMACHI 2-CHOME, CHIYODA TOKYO, JAPAN.

Inventors:


- (a) TOICHI HIRATA.
- (b) DEAKI TANAKA.
- (c) KAZUNORI NAKAMURA.
- (d) HIDESHI KOIWAI.
- (e) YONEAKI TAKAHASHI.

Application No. 197/Cal/1991 filed on 5th March 1991.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta.

4 Claims

A hydraulic drive system for hydraulic machine comprising a hydraune fluid supply source having at least one hydraulic pump, a reservoir, at least one hydraulic actuator, a hydraulic fluid supply line connected to said hydraulic fluid supply source, a hydraulic fluid return line connected to said reservoir, a flow control vatve having a first variable restrictor to control a flow rate of a hydraulic fluid supplied from said supply line to said hydraulic actuator and a second variable restrictor to control a flow rate of the hydraulic fluid discharged from said hydraulic actuator to said return line, a pressure compensating valve disposed in said supply line to hold constant a differential pressure across said first variable hold constant a differential pressure across said lifst variable restrictor, and a recovery circuit including a recovery line having a check valve allowing only a flow of the hydraulic fluid toward said supply line, for receiving at least part of the hydraulic fluid discharged from said hydraulic actuator and returning it to said supply line at a portion between said pressure compensating valve and said first variable restrictor upon controlling of the discharged flow rate by said second variable restrictor to thereby recover the discharged hydraulic fluid. restrictor to thereby recover the discharged hydraulic fluid, characterized in that said recovery circuit further includes a third variable restrictor for controlling a recovery pressure of the hydraulic fluid returned to said supply line, and means for controlling an amount of restriction of said third variable restrictor dependent upon an input amount of said flow rate control valve.



Int. Cl.: F 15 C 1/00.

HYDRAULIC MOTOR DRIVE CIRCUIT SYSTEM FOR EXAMPLE IN A HYDRAULIC EXCAVATOR.

Applicant: HITACHI CONSTRUCTION MACHINERY CO. LTD., OF 6-2, OHTEMACHI 2-CHOME, CHIYODA-KU, TOKYO, JAPAN.

Inventors:

- (1) HITOSHI KAGIWADA.
- (2) TOMOHIKO YASUOKA.

Application No. 198/Cul/1991 filed on 5th March 1991.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta,

20 Claims


A hydraulic—motor drive circuit system in a hydraulic excavator comprising a hydraulic motor (1) for rotatively driving an inertia load (2), a hydraulic pump (4) serving as a main hydraulic source, a reservoir (5), a pair of main lines (3A, 3B) through which said hydraulic motor is connected to said hydraulic pump and said reservoir, and a directoinal control valve (6) arranged in said pair of main lines for switching a direction of hydraulic fluid supplied to said hydraulic motor from said hydraulic pump, characterised in that the system comprises:

an auxiliary hydraulic source (29);

an auxiliary line (30) having one end thereof connected to said auxiliary hydraulic source;

low-pressure selecting means (26) connected to the other end of said auxiliary line and said pair of main lines (3A, 3B) for causing the other end of said auxiliary line to communicate with one of said pair of main lines on the low pressure side during rotation of said hydraulic motor (1); and

switching control means (59) arranged in said auxiliary line for supplying the hydraulic fluid from said auxiliary hydraulic source to the other end of said auxiliary line when said directional control valve (6) is at least in a neutral position, and cutting off the supply of the hydraulic fluid from said auxiliary hydraulic source to the other end of said auxiliary line when said directional control valve is in an operative position.



Cl.: 170 A

176524

Int. Cl4: A 47 K 5/14.

A 47 L 17/00.

ABRASIVE ARTICLE FOR CLEANING OF MODE-RATELY SOFT METALLIC SURFACES.

Applicant: GIGI PRODUCTS, INC., OF ZONA FRANCA INDUSTRIAL, APARTADO 850, SAN PEDRO DE MACORIS. REPUBLIC OF DOMINICA.

Inventor: HENRY MATTESKY.

Application No. 472/Cal/1991 filed on 21st June 1991.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta.

25 Claims

An open low density abrasive article adapted for the cleaning of moderately soft metallic surfaces comprising at least one layer of a substrate selected from the group consisting of (i) a lofty open non-woven three dimensional web form substrate of a plurality of interlaced randomly extending flexible durable, tough, resilient organic fibers having a diameter of from 25 to 250 microns,

said web fibers firmly being adhesively bonded together at points where they cross and contact each other to form a three-dimensionally integrated structure throughout said web,

there being defined throughout said article a tridimensionally extending network of intercommunicating voids constituting the major portion of the volume of the said article,

said article being flexible and readily compressible and, upon release of pressure capable of recovering substantially completely to its initial form, the interstices between adjacent fibres being open and substantially unfilled by binder or abrasive.

- (ii) a polymeric flexible foam selected from the group consisting or urethane, polypropylene, polyethylene, polyvinyl alcohol silicone rubber, neoprene and natural rubber altex of density between 0.015g/cm3 and 0.1 g/cm3,
- (iii) woven fabrics of natural and synthetic fibers selected from the group consisting of terry, duck, twill, oznaberg, and leno of surface density between 100g/m² and 410g/m²,
- (iv) non-woven fabrics of natural and synthetic fibers selected from the group consisting of spunbonded, fibre entangled, thermal and chemical bonded and needle punched of surface density between 75g/m² and 285g/m², and
- (v) high wet strength, substantially water resistant papers of the kraft or zinc chloride treated type of surface density from 100g/m³ to 1Kg/m³; and abrasive particles such as finely divided copper alloy, iron, nickelalloy, spherical glass beeds or steel distributed upon and within said substrate and firmly bonded to the substrate fibres by a relatively hard binder such as herein described, said abrasive being defined by any one of the measures of hardness selected from the group of measures consisting of:
 - (a) Mho's 4.5-6.3.
 - (b) Rockwell B 60-85.
 - (c) Brinell 95--142.
 - (d) Knoop 120-180.

and-optionally a lubricant such as herin described.

Cl.: 155 E

176625

Int. Cl.: D 04 H 1/22.

IMPROVEMENTS IN OR RELATING TO A NON-WOVEN THREE-DIMENSIONAL FABRIC.

Applicant: JOHNSON & JOHNSON INC., OF 2155 BOULEVARD PIE IX, MONTREAL, QUEBEC, CANADA H1V 2E4.

Inventors:


- (1) ROGER BOULANGER.
- (2) DANIEL PLOURDE.
- (3) ANDRE BROUSSEAU.
- (4) FLAVIO METTA.


Application No. 503/Cal/1991 filed on 3rd July 1991.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta.

35 Claims

A nonwoven three-dimensional fabric comprising a unitary reticular network of fibers in an engagement with one another by the influence of fluid forces, defining a pre-determined pattern of blind holes, each hole extending transversely to the plane of the fabric and containing a protuberant fiber packing at a close end thereof, one side of said fabric containing a pattern of recesses corresponding to opening of said blind holes, the other side of said fabric having a knobby surface enotaining apexes of the protuberant fiber packings.





Cl.: 74

176626

Int. Cl.⁴: B 41 N 9/00.

A METHOD OF FABRICATING A LOOPED NON-POROUS BLANKET FOR AN EXTENDED NIP PRESS.

Applicant: BELOIT CORPORATION, OF 1 ST. LAW-RENCE AVE. BELOIT, WI 53511, U.S.A.

Inventors:

- (1) PAUL MCCARTEN.
- (2) EUGENE LOUIS SLAGOWSKI.

Application No. 530/Cal/1991 filed on 9th July 1991.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rule 1972), Patent Office, Calcutta.

4 Claims

A method of fabricating a looped non-porous blanket for an extended nip press which includes a shoe and a felt said method including the sequential steps of:

weaving a base from a first plurality of filaments such as:
herein described disposed in a machine direction and a
second plurality of filaments such as herein described
disposed in a cross-machine direction, said first plurality
of filaments having a modulus of elasticity which permits flexing of the balnket during movement of the
blanket through the extended nip press, atleast one portion of the second plurality of filaments having a modulus of elasticity which is higher than the modulus of
elasticity of the first plurality of filaments for inhibiting
flexing of the blanket in a cross-machine direction;

simultaneously saturating the woven base on both sides thereof with polyurethane;

wrapping the saturated woven base around a smooth mandrel:

heating the wrapped mandrel until the polyurethane gels;

further heating the wrapped mandrel within a heating oven for curing the polyurethane;


cooling the cured blanket;

grinding in known manner the blanket to a uniform thick-

grooving in known manner the outer surface of the blanket while the blanket is still supported on the mandrel; and

removing the finished blanket from the mandrel.

FIG. 1



(Compl Speen, 23 pages;

Drgns, 4 sheets)

Cl.4: 32+E & 40 B

176627

Int. Cl.4: C 08 F 210/02, 4/64, 4/78.

A PROCESS FOR COPOLYMERIZING ETHYLENE.

Applicant: PHILLIPS PETROLEUM -COMPANY, -OP BARTLESVILLE, STATE OF OKLAHOME, UNITED STATES OF AMERICA

Inventors: (1) ELIZABETH ANN BENHAM (2) MAX PAUL MCDANIEL.

Application No. 643/Cal/1991 filed on 30th August, 1991.

Appropriate office for opposition proceedings (Rule 4, Patent Rule 1972) Patent Office, Calcutta,

11 Claims

A process for copolymerizing ethylene and at least one comonomer which is an alpha monoolefin or an alpha, omega diolefin containing 3 to 18 carbon atoms, which comprises contacting said ethylene and said at least one comonomer in a liquid diluent under particle form polymerization conditions in the presence of a mixture of a particulate titaniumcontaining catalyst and a particulate chromium containing catalyst and an organometallic cocatalyst for the titanium containing catelyst, wherein the particulate chromium containing catalyst comprises an inorganic oxide support known per se and chromium, said chromium-containing catalyst containing about 0.1 to about 10 weight percent chromium and wherein the weight ratio of titanium-containing catalyst to the chromium-containing catalyst is in the range of from about 80: 20 to about 20: 80, wherein said titanium-containing catalyst is prepared by reacting a titanium alkixide with amgnesium dichloride in a substantially anhydrous organic liquid, for example, as herein described, to obtain a solution wherein said titanium alkoxide is a titanium tetraulkoxide having an alkyl group containing 1 to 10 carbon atoms and the molar ratio of the titanium alkoxide to the magnesium dichloride is within the range of about 10: 1 to about 1: 10; contacting said solution with a hydrocarbyl aluminium halide of the formula R_m AlX_{3-n} wherein R is an alkyl group having 1 to 8 carbon atoms, X is chloride and m is a number in the range of 1 to 3 and to produce a precipitate wherein the molar ratio of the titanium alkoxide to the hydrocarbyl aluminium halide is within the range of about 10: 1 to about 1: 10 and wherein said precipitate is contacted first with titanium tetrachloride and then with a trielkylaluminium compound in which the alkyl groups contain 1 to 4 curbon atoms,

wherein if desired said titanium catalyst contains olefinic propolymer, wherein the olefin used to form the prepolymer is an aliphatic mono-1-olefin which is present in an amount in the range of from about 1 to about 50 weight percent based on the total weight of the final prepolymerized catalyst, wherein the molar ratio of the comonomer to the ethylene is in the range of about 99: 1 to about 1: 99, wherein said liquid diluent contains no more than about 20 parts per

million of said organometallic cocatalyst and that the polymerization is conducted at a temperature in the range of from about 140°F to about 230°F, and a pressure in the range of from about 110 to about 700 psia for a time in the range of from about 0.5 to about 2 hours.

(Compl. Specn. 26 pages,

Drgns. Nil.)

Cl.: 39 P

176628

Int. Cl.: C 01 F 7/74

THE PREPARATION OF LOW IRON CONTENT ALU-MINIUM SULPHATE FROM FLY ASH.

Applicants & Inventors: DEBASIS GOSWAMI, NTPC/FSTPP (D.M. PLANT) P.O. NABARUN, DISTRICT MURSHIDABAD (WB), PIN-742 236, INDIA, AND RAMNARAYAN LAL SHRIVASTAVA, NTPC/FSTPP (D.M. PLANT) P.O. NABARUN, DISTRICT MURSHIDABAD (WB), PIN-742 236, INDIA.


Application No. 663/Cal/1991 filed on 4th September, 1991.

Appropriate office for opposition proceedings (Rule 4, Patents Rule, 1972) Patent Office, Calcutta.

5 Claims

A process for the production of Alumino-Ferric from fly ash (coal ash), generated in thermal power stations, which comprises:—

- (a) Separating the Alumina rich part of fly ash in a fluidised bed water column, maintaining up flow rate of 20 lit/min. to 60 lit./min. inside the column as described herein.
- (b) Separating magnetites inpurities of Alumina rich part, obtained after step 1(A), by a suitable wet magnetic separator to obtain less fron contaminated Alumina rich fraction,
- (c) Reacting the mass, obtained after step 1(B), with 20% to 60% volume; volume Hydrochloric Acid to further reduce impurities of magnetites or Iron Oxides,
- (d) Reacting Alumina rich part, collected after step 1(C), with 40% to 100% volume: volume Sulphuric Acid to produce a solution of Aluminium Sulphate within a temperature range from 60°C to 240°C and within a time period from 15 minutes to 120 minutes,
- (e) Cooling the reaction mixture, obtained from step 1(D), below 100°C, diluting with water and using suitable coagulants to enhance separation of unreacted Silicius matter.
- (f) Concentrating the solution, obtained from 1(E), in an evaporator to a specific gravity 1,2 to 1.6, the neutralisation of excess acidity being carried out with Hydrated Alumina and the evaporation continued until reaches the specific gravity values from 1.8 to 2.2.
- (g) Recovering of Aluminium Sulphate slab with very low Iron after easting in casting trays.



(Compl. Specn. 13 pages,

Drgns. 3 sheets.)

Cl.: 206 E

176629

Int, Cl.4: H 04 B 1/54

APPARATUS FOR TWO-WAY COMMUNICATION.

Applicant: CEDCOM NETWORK SYSTEMS PTY. LIMITED, OF 203-205 DARLING STREET, BALMAIN, N.S.W. 2041, AUSTRALIA.

Inventors: PAUL ANTON SYSEN, RAPHAEL TOBIAS.

Application No. 779/Cal/1991 filed on 15th October, 1991.

(Convention No. P15107/87 on 27-10-87; P18011/88 on 02-05-88; P18687/88 on 08-06-88; PJ 0632/88 on 27-09-88; all are in Australia.

(Divided out of Application No. 890/Cal/88 antidated to 27-10-88).

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office. Calcutta,

3 Claims


Apparatus for two-way communication between a transmitter/receiver unit, called a controller, and at least one second transmitter/receiver unit, called a communicator. said controller comprising:

- (a) first means for generating a carrier signal:
- (b) second means for modulating said carrier signal with a first informational signal to produce a first modulated carrier signal;
- (c) third means for transmitting said first modulated carrier signal as a first electromagnetic wave signal to said communicator:
- (d) fourth means for receiving a second electromagnetic wave signal, transmitted by said communicator to reproduce a second modulated carrier signal; and

- (•) fifth means for demodulaing said second modulated carrier signal to reproduce a second informational signal; each of said communicators comprising:
 - (a) sixth means for receiving said first electromagnetic wave signal transmitted by said controller to reproduce said first modulated carrier signal;
 - (b) seventh means for demodulating said first modulated carrier signal to reproduce and first informational signal;
 - (c) eighth means for backscatter modulating said first modulated carrier signal with a second informational signal to produce a second modulated carrier signal; and
 - (d) ninth means for transmitting said second modulated carrier signal as said second electromagnetic wave signal;

the improvement wherein said first means comprises means for pseudo-randomly varying the frequency or phase of said carrier signal and said fifth means also having means for mixing said carrier signal with said second modulated carrier signal,

thereby to provide security against jamming, eavesdropping, and range gating on said first or second electromagnetic wave signal.



(Compl. Spec v. 68 pages,

Drgns, 18 sheets.)

Cl. . 206 E

176630

Int. Cl.4 : H 04 B 1/54

APPARATUS FOR TWO-WAY COMMUNICATION.

Applicant: CEDC OM NETWORK SYSTEMS PTY, LTD., OF 203-205 DARLIN IG STRFET, BALMAIN, N.S.W. 2041, AUSTRALIA.

Inventors: (1) PAU IL ANTON NYSEN

(2) RAF HAEL TOBIAS.

Application No. 780/C M/1991 filed on 15th October, 91.

(Convention No. PI 516 77/87 on 27-10-87; PI 8011/88 on 02-05-88; PI 8687/38 on 03-06-88; PJ 0632/88 on 27-09-88, all are in Australia).

(Divided out of No. 891) (Cal/88 antidated to 27-10-88).

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

5 Claims

An apparatus for two-way communication between a transmitter/receiver unit, called a controller, and at least one second transmitter/ receiver unit, called a communicator, said controller comprising:


- (a) frequency generator for generating a carrier signal;
- (b) first modulator for modulating said carrier signal with a first informational signal to produce a first modulated carrier signal;
- (c) first transmitter for transmitting said first modulated carrier signal as a first electromagnetic wave signal to said communicator;
- (d) first receiver for receiving a second electromagnetic wave signal transmitted by said communicator to reproduce a second modulated carrier signal; and
- (e) first demodulator for demodulating said second modulated carrier signal to reproduce a second informational signal:

each of said communicators comprising :

- (a) second receiver for receiving said first electromagnetic wave signal transmitted by said controller to reproduced said first modulated carrier signal;
- (b) second demodulator for demodulating said first modulated carrier signal to reproduce said first informational signal;
- (c) backscatter modulating for backscatter modulating said modulated carrier signed with a second informational signal to produce a second modulated carrier signal; and
- (d) second transmitter for transmitting said second modulated carrier signal as said second electromagnetic wave signal;

the improvement wherein said second receiver and said second transmitter comprise a common antenna, a common quadrature polarization change over switch and first and second feed line means connecting said change over switch said antenna

with orthogonal first and second feed points respectively on said antenna, said antenna being a pitch antenna and said orthogonal first and second feed points are 90" a part around the edge of the said antenna with respect to its centre, said frequency generator comprises means (24) for pseudo-rahdomly varying frequency or phase of said carrier signal and said first demodulator having means (11) for mixing said carrier signal with said second modulated carrier signal, thereby to provide security against jamming, cavesdropping, and range gating on said first and second electromagnetic wave signal.



(compl Speen, 68 pages

Diwgms, 18 Sheets.)

Ind. Cl.: 172-D^o

Int, Cl. 1. D 01 H 9/08

AUTO DOFFING DEVICE IN CAP SPINNING MACH-INE.

Applicant: MASCHINENFABRIK RIETER AG., A BODY CORPORATE ORGANISED UNDER THE LAWS OF SWITZERLAND, OF CH-8406 WINTERTHUR, SWIT-ZERLAND.

Inventors; (1) LUDEK MALINA

(2) RAINER BUSCH


(3) ANDRE LATTION.

Application No. 195/Mas/90 tiled March 15, 90.

Appropriate Office for Opposition proceedings (Rule 4, Patents Rules, 1972), Patent Office, Madras Branch.

10 Claims

Auto doffing device in cap spinning machine comprising a gripping means (19) for guiding the tubes and the removal of the packages, a holding means (28) for holding the tubes above the packages and a means for separating the packages and the cap.



(Com. 13 pages;

Diwgs. 3 Shorts.)

Ind. Cl.: 84-B

176632

Int. Cl.4 : C 10 L 1/00

A METHOD AND A DEVICE FOR PROBUCING HYD-ROCARBON FUEL WITH IMPROVED COMBUSTIBI-LITY.

Applicant: SHINFUJI KOGYO KABUSHIKI KAISHA, A CORPORATION OF JAPAN, OF 7-6, 3-CHOME TFN-MA, KITA-KU, OSAKA-SHI, OSAKA-FU, JAPAN,

Inventor: TETSUO SAKUMA.

Application No. 282/Mas/90 filed April 16, 90.

Appropriate Office for Opposition proceedings (Rule 4, Patent's Rules, 1972), Patent Office, Madras Branch.

5 Claims

A method of producing a hydrocarbon fuel with improved combustibility comprising exposing the hydrocarbon fuel to a magnetic field of a magnet having a magnetic flux density of 5 to 18 gauss at the S pole and a magnetic flux density of less than 6 gauss at the N pole and the ratio of the magnetic flux density at the N pole to the magnetic flux density at the \$ pole does not exceed 0.5.

(Com. 34 pages)

Ind. Cl. . 154-E

176633

Int. Cl.1: G 07 B 17/00

A DIGITAL MARK-PRINTER.


Applicant & Inventor: WU SHENG-JUNG, A CITIZEN OF THE REPUBLIC OF CHINA, OF 4FL.27. LANE 160, HSIN SHENG S ROAD, SEC. 1, TAIPEI, TAIWAN, RE-PUBLIC OF CHINA.

Application No. 295/Mas/90 filed April 18, 90.

Appropriate Office for Opposition Proceedings 4 Patents Rules, 1972), Patent Office, Madras Branch.

20 Claims

A digital mark-printer comprising a central processing unit (CPU) with a main control program having a microprocessor main control module; a parallel bus; a parallel bus interface circuit means connected to said central processing unit through said parallel bus, with a sensor circuit means and a driver circuit means; said sensor circuit means has a keyboard interface circuit means and a driver index interface suid driver circuit means circuit means first driver circuit means and a second driver circuit means; and a main shaft with a printing head having a plurality of numeral wheels, driven by said first and second driver circuit means and said driver index interface circuit means.



(Compl. Speen, 22 pages;

Drgws. 12 sheets.)

Ind. Cl.: 107-C

176634

Int. Cl.4: F 02 B 23/00

AN IMPROVED CYLINDER HEAD FOR INTERNAL COMBUSTION ENGINE.

Applicant & Inventor: ISSAC STANLY, KUTTIVILA VEEDU, KANJIRACODE, KUNDARA P.O., QUILON DISTRICT, KERALA, AN INDIAN CITIZEN.


Application No. 318/Mad/90 filed April 24, 90.

Appropriate Office for Opposition Proceedings (Rule 4 Patents Rules, 1972), Patent Office, Madras Branch.

2 Claims

An improved cylinder head for internal combustion engine characterised in that the conventional cylinder head (1) is provided with at least one conical recess (4) on the inner

wall of the cylinder, the axis of the conical recess being perpendicular to the top surface of the piston and the clearance volume of the cylinder head is 3 to 9 times the total volume of all the said conical recesses.



(Compl. 14 pages;

Drgws. 1 sheet.)

Ind. Cl.: 76-B

176635

1nt. Cl.4 . A. 44 B 21/00

A DOUBLE-MOUTHED CLIP.

Applicant: AGUSTIN GARCIA CRESPO, A SPANNISH CITIZEN OF LA CALDERONA SONO, 39500 CABEZON DE LA SAL. (CANTABRIA), SPAIN.


Inventor: AGUSTIN GARCIA CRESCO.


Application No. 350/Maa 90 filed 08 May, 90,

Appropriate Office for Opposition Proc.edings (Rul-Patents Rules, 1972), Patent Office, Madras Branch.

9 Claims

A double-mouthed clip comprising a pair of identical law pairts, each of said jaw parts having a symmetrical, elongated shape with a first end, a second end and a cen'ral saw-toothed portion wherein said central portion has a substantially constant thickness and said jaw part tapers in thickness from said central portion to said first end and said second end; and means for urging said jaw parts together so that said sawtoothed portions face each other and act as vipvots on both ends of said clip.





(Com. 9 pages;

Drgw. 1 Sheet.)

Ind. Cl.: 158-Ba

176636

Jnt. €l.4 : B 61 G 9/00.

A DRAWBAR COUPLER FOR A RAILWAY CAR.

spilicant: NicCONWAY & TORLLYCORPORATION, OF 109, 48TH STREET, PITTSBURGH, PENNSYLVANIA 15201, U.S.A., A U.S. CORPORATION.

Inventor: MARY ANN GLOVER.

Application No. 361/Mas 20 wied May 11, 90.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972), Patent Office, Madras Branch.

12 Claims

A drawbar coupler for a radway car having a centro sill, caid drawbar coupler comprising; a drawbar having a veriteal pin hole extending between top and bottom surfaces forwardly of a turncated, spherically shaped buff load transfer surface at a butt end portion thereof, rear support block having a truncated, substantially hem-spherically shaped buff load bearing at face engageable with said truncated spherically shaped buff load transfer surface, and a tapered rear surface, a carrier housing attached in a centre stil Ifor transferring buff and draft loans from said drawbar to said centre sill, carrier housing having openings for receiving a drawbar pin, a drawbar bearing block having a rearwardly facing draft load transfer surrace engaged with said drawbar in said vertical pin hole, said drawbar bearing block further having a forwardly facing draft load transfer surface, a drawbar pin said charler housing openions having an annular pin surfact engaged with sold forwardly facing draft load transfer surface of said drawbar bearing block, said drawbar pin being egoratively connected to said carrier housing for transferring draft forces from said drawbar to said centre sill; and a gravity responsivety stack adjusting wedge for engaging said

(Com. 15 pages;

Drwgs, 3 Sheets.)

Ind, Cl.: 190 A&B

176637

Int. Cl.4 ; F 23 R 3/46.

COMBUSTION CHAMBER OF A GAS TURBINE.

Applicant: ASEA BROWN BOVERI LTD., A SWISS COMPANY OF BADEN/SWITZERLAND.

Inventor: JOCOK KELLER.


Application No. 371/Mas/90 filed May 15, 90.


Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972), Patent Office, Madras Branch.

8 Claims

A combustion chamber of a gas tutbine wherein the combuction chamber (A) being provided at the burner air inlet flow end with a number of premixed burners (B, C) located adjacent to one another and, with respect to the burner air flowing through them; of different sizes, the large premixed

burners (B) and the small premixed burners (C) are positioned alternatively and air nozzles (F) being placed between the individual premixed burners (B, C).





(Com, 15 pages;

Drwgs, 5 Sheets, 8

Ind. Cl.: 48 Aa

176638

Int. Cl.): F 16 G 11,00.

A METHOD OF MAKING CABLE-JOINTS BY JOINING ENDS OF PAPER INSULATED CABLES AND ENDS OF JELLY FILLED CABLES AND THE CABLE-JOINTS OBTAINED THEREBY.

Applicant & Inventor: NARENDER SURANA, OF INDIA EXTRUSION, SURYA TOWERS, 5TH FLOOR, SARDAR PATEL ROAD, SECUNDERABAD-500 003, ANDHRA PRADESH, INDIA, AN INDIAN NATIONAL.

Application and Provision Specification No. 435/Mas/90 filed June 4, 90.

Complete Specification left: September 2, 1991.

Appropriate Office for Opposition Proceedings (Rule 4 Patents Rules, 1972), Patent Office, Madras Branch.

7 Claims

A method of making cable joints by joining ends of paper-insulated cables on one side and ends of jelly-filled cables, on the other to provide a water or moisture proof cable joint which comprises creating water barriers at both the joining ends of the expective cables, the said water barrier being provided (1) on the paper insulated cable ends by coating the exposed metal ends or the insulation-free ends of the paper insulated cables with water repellant micro-crystalline wax followed by applying an insulation tape, and (11) on

the jelly-filled cable ends by providing a packing of water-swellable powder on the exposed jelly-free, insulation-free ends of the cables, and thereafter joining the respective pairs of cables ends in the usual manner, connecting the aluminium foil ends of the two cable ends in the usual manner by using metal connectors, applying insulation tape on the aluminium foil ends, and thereafter applying cloth tape followed by applying cannister and heat shrinkable sheath in the usual manner

(Prov. 9 pages; Com 1.3 pages; Drwgs. 3 Sheets.) (Prov. Drwg 1 Sheet, Comp Drwg 2 Sheets),

Ind. Class: 126-A

176639

Int. Cl.4: G 01 R 19/02.

A DEVICE FOR MEASURING THE RMS VALUE OF A SIGNAL.

Applicant: MERLIN GERIN, OF 2 CHEMIN DES SOURCES, F 38240 MEYLAN, FRANCE, A FRENCH COMPANY.

Inventor: DIDIER FRAISSE.

Application No. 575/Mas/90 filed July 18, 1890.

Appropriate Office for Opposition Proceedings (Rule 4 Patents Rules, 1972), Patent Office, Madras Branch.

6 Claims

A device for measuring the rms value of a signal, notably for current measurement in a solid-state trip device, comprising a full-wave rectifier circuit (10) having an input receiving an input signal (I, VI) to be measured and an output providing rectified signal (V2), a first order low-pass filter (12) having an input connected to the output of rectifier circuit for receiving a rectified signal (V2) and an output for providing a filtered signal (V3), and a peak detector (14) having an input connected to the output of the low-pass filter for receiving a filtered signal (V3) and an output providing an output signal (V4) representative of the rms value of the input signal I, (V1), the filter cut-off pulse (WC) being comprised between $4\pi f/6$ and $4\pi f/5.33$, f being the fundamental frequency of the input signal designed to be applied to the device.

(Com. 15 pages;

Drwgs .3 Sheets.)

Ind. Class: 94-G.

176640

Int Cl.4: B 02 C 9/00.

A MACHINE FOR METERING AND GRINDING FRIABLE MATERIAL.

Applicant: SOCIETE DES PRODUITS NESTLE S.A.. A COMPANY INCORPORATED IN SWITZERLAND, OF CASE POSTALE 353, 1800 VEVEY, SWITZERLAND.

Inventor: MARCEL BUHLER.


Application No. 800/Mas/90 filed October 9, 1990.

Appropriate Office for Opposition Proceedings (Rule 4, Patents ules, 1972), Patent Office, Madras Branch.

4 Claims

A machine for metering and grinding friable material, comprising a metering screws (1), a beater (2) formed by bars (3) which are integral with the helical periphery of the downstream end of the screw (1), the said bars are parallel to the axis (4) of the screw and distributed at the pieces of a regular polygon centred on the said axis, a cylindrical

housing (5) surrounding the screw (1) and a cylindrical screen (6) extending the housing (5) and at least partly surrounding the beater (2).



'(Com. 8 pages;

Drwgs. 2 Sheets.)

AMENDMENT PROCEEDING UNDER SECTION 57

The amendment proposed by Siemens Aktiengesellschaft of Wittelsbacherplatz 2, D-8000 Munchen 2, West Germany, A West German Company, As Advertised in the Part III, Section 2 of the Gazette of India dated 16-3-96 in respect of application for Patent No. 175625, no opposition being filed within the stipulated period the said amendments have been allowed.

RESTORATION PROCEEDINGS

Notice is hereby given that an application for restoration of Patent No. 157958 dated the 10th Dec. 1982 made by Topy Industries Ltd. on the 14th Nov., 95 and notified in the Gazette of India Part III, Section 2, dated the 25-2-96 has been allowed and the said Patent restored.

Notice is hereby given that an application for restoration of Patent No. 160611 dated the 21st Jan. 1985 made by Krishna Kumar Rai on the 23rd Nov., 1995 and notified in the Gazette of India Part III. Section 2, dated the 25-2-96 has been allowed and the said Patent restored.

Notice is hereby given that an application for restoration of Patent No. 169340 dated the 9th Jan., 1989 made by Dev Dutt Mohanty on the 6th September, 1995 and notified in the Gazette of India Part III, Section 2 dated the 17th Feb., 1996 has been allowed and the said patent restor-

Notice is hereby given that an application for restoration of Patent No. 171058 dated the 7th Nov., 1989 made by Victory Gus Alaram Company on the 31st August, 1995 and notified in the Gazettt of India Part III, Section 2, dated the 28-10-1995 has been allowed and the said Patent restored.

OPPOSITION PROCEEDINGS UNDER SECTION 25(1)

An Opposition has been entered on 20-6-1996 by M/s. Unique Pharmaceutical Laboratories Ltd. to grant of a Patent on Application No. 176188 (730/Cal/93) dated 26th Nov., 93 made by F. H. Faulding & Co. Ltd.

RENEWAL FEES PAID

157021 157451 158186 158258 158407 158614 161367 161626 161719 162058 162988 163004 163013 163014 163342 163504 163602 163860 164321 164612 165045 165323 165470 165488 165535 165864 165886 165981 166063 166219 166298 166339 166649 166892 167056 167164 167363 167631 167691 167810 167889 168084 168085 168086 168112 168425 168436 168574

 168643
 168859
 168858
 168915
 169028
 169105
 169230
 169458

 169892
 169900
 170296
 170355
 170356
 170359
 170371
 170374

 170400
 170410
 170516
 170517
 170521
 170541
 170636
 170782

 170883
 171057
 171140
 171209
 171232
 171440
 171445
 171508

 171620
 171733
 171934
 171965
 172237
 172438
 172642
 172698

 172815
 172819
 173108
 173161
 173378
 173587
 173647
 173648

 173709
 174063
 174081
 174094
 174101
 174116
 174295
 174581

 174382
 174583
 174586
 174587
 174588
 174589
 174590
 175048

 175198
 175335
 175338
 175541
 175544
 175547
 175551
 175621

PATENT SEALED ON 12-07-1996

169586 175992 176058*D 176059*F 176073 176076 176089 176096 176131 176132* 176134 176139 176145 176148*D 176150*D 176151 176152 176154 176155 176156 176157 176158 176159 176160.

CAL-05, DEL-19, BOM-NIL, MAS-NIL

*Patent shall be deemed to endorsed with the words LICENCE OF RIGHT Under Section 87 of the Patents Act, 1970 from the date of exiration of three years from the date of sealing.

D-Drug Patents, F-Food Patents.

REGISTRATION OF DESIGNS

The following designs have been registered. They are not open to inspection for period of two years from the date of revisitation except as provided for in Section 50 of the Design Act, 1911.

The date shown in the each entries is the date of the registration included in the entries.

- Class 1. Nos. 170317 & 170318, Dan Efinim Alpert, a citizen of Israel, of 16055, Ventura Boulevard, Apartment No. 425, Encino, California 91436, U.S.A. and AVI KATZ, a citizen of Israel, of 63/15 Harav Kook St., Netanya 42260, Israel, "FOUR STONE DEAMOND", 29th November 1995.
- Class I. No. 170334, Noothigattu Venkata Sutyanarayana, an Indian of C/o N. Venkataramana, Main Road, Thallapalem, Kasim Kota Mandal, Anakapalli (TQ), Vizag (Dt), A.P., India, Pin Code No. 531037, "PORTABLE POWER GENFRATOR BY USING WIND", 1st Dec., 95.
- Nos. 170451 & 170452, Chief Controller, Department of Defence Research and Development, Defence Research and Development Organisation, M/o Defence, Govt. of India, Sena Bhawan, New Delhi 110011, "CASING FOR FUSE", 26th December 95.
- Class 3. Nos. 170453 & 170454, Chief Controller, Department of Defence Research and Development, Defence Research and Development, Organisation, M/o. Defence, Government of India, Sena Bhawan, New Delhi-110 011, "CASING FOR FUSE", 26th December 1995.
- Class 3. Nos. 170455 to 170457, Chief Controller, Department of Defence Research and Development,
 Defence Research and Development Organisation,
 M/o, Defence, Govt. of India, Sena Bhawan, New

- Delhi-110 011, "FUSE CASING", 26th December 1995
- Class 3. Nos. 130248 & 170249, Motor-S.a., a French company of 119, Benlevard Felix Faure, 53,300, Aubervilliers, Franco, "CONTAINER", 20th November 1995.
- Class 3. No. 170323, Noothigattu Venkata Satyanarayana, an Indian of C/o N. Venkataramana, Main Road. Thallapalem, Resim Kota, Mandal, Anal.apalli (TQ), Vizag (Dr), A.P., India, Pin Code No. 531037, "MULTIPIN BATTERY CHARGER", 29th Nov. 95.
- Class 3. No. 170324, Noothigattu Venkata Satyanarayana, an Indian of C/o N. Venkataramana, Main Road, Thallapalem, Kasim Kota Mandal, Anakapali (TQ), Vizag (Dt), A.P., India, Pin Code No. 531037, "RECHARGEABLE HAND FAN", 29th Nov 95.
- Class 3. No. 170325, Noothigattu Venkata Satyanurayana, an Indian of C/o N. Venkataramana, Main Road, Thallapalem, Kasim Kota Mandal, Anakapali (TQ), Vizag (Dt), A.P., India, Pin Code No. 531037, "RECHARGEABLE HAND FAN WITH CHARGER HAVING DETATCHABLE MULTIPIN CORD", 29th Nov 95.
- Class 3. No. 170326, Noothigattu Venkata Satyanarayana, Indian of C/o N. Venkataramana, Main Road, Thallapalem, Kasim Kota Mandal, Anakapal'i (TQ), Vizag (Dt), A.P., India, Pin Code No. 531037, "FAN BLADE", 29th Nov 95.
- Class 3. No. 170327, Noothigattu Venkata Satyanarayana, Indian of C/o N. Venkataramana, Main Road, Thallapalem, Kasim Kota Mandal, Anakapal'i (TQ), Vizag (Dt), A.P., India, "RECHARGE-ABLE MINI LUQUID MIXER WITH SOCKET (FOR POWER TAPPING)", 29th November 1995.
- Class 3. No. 170329, Noothigattu Venkata Satyanarayana, Indian of C/o N. Venkataramana, Main Road, Thallapalem, Kasim Kota Mandal, Anakapalli (TQ), Vizag (Dt), A.P., India, "RECHARGE-ABLE HAND FAN WITH MULTIPIN CORD

- FOR AUDIO BACK UP", 29th November 1995.
- Class 3. No. 169953, Crystal Plastics & Metallizing Pvt. Ltd., at Sanghi House, Palkhi Galli, Off Veer Savarkar Mäng, Prabhadevi, Bombay-400 025, Maharushtra, India, "COMB", 4th October 1995.
- Class 3. No. 169638, Crystal Plastics & Metallizing Pvt. Ltd., at Sanghi House, Palkhi Galli, Off Veer Savarkar Marg, Prabhadevi, Bombay-400 025, Maharashtra, India, "COMB", 8th August 1995.
- Class 3. No. 169795, Crystal Plastics & Metallizing Pvt. Ltd., at Sanghi House, Palkhi Galli, Off Veet Savarkar Marg, Prabhadevi, Bombay-400 025, Maharashtra, India, "COMB", 5th September 1995.
- Class 3. No. 169803, Standipack Pvt. Ltd., an Indian company of Community Centre, East of Kailash, New Delhi-110 065, India, "POUCH", 6th September 1995.
- Class 3. No. 170053, Standipack Pvt. Ltd., an Indian company of Community Centre, East of Kailash, New Delhi-110-065, India, "POUCH", 18 Oct., 1995.
- Class 3. No. 169877, Standipack Pvt. Ltd., an Indian company of Community Centre, East of Kailash, New Delhi-110 065, India, "POUCH", 21st September 1995.
- Class 4. Nos. 170437 to 170439, 170441 & 170442, H. R. & Johnson (India) Ltd... a company incorporated under the Indian Companies Act, 1956 whose address is Kakad Chambers, 132, Dr. Annie Besant Road, Worli, Bombay-400 018, Maharashtra, India, "TITLE", 21st December 1995.

T. R. SUBRAMANIAN introller General of Patents, Designs & Trade Marks